

PRIME WebSocket Automation Interface Reference Guide

Version 4.10.7

January 2025



Chyron PRIME WebSocket Automation Interface Reference Guide • 4.10.7 • January 2025
This document is distributed by Chyron in online (electronic) form only, and is not available for purchase in printed form.

This document is protected under copyright law. An authorized licensee of Chyron PRIME WebSocket Automation Interface may reproduce this publication for the licensee's own use in learning how to use the software. This document may not be reproduced or distributed, in whole or in part, for commercial purposes, such as selling copies of this document or providing support or educational services to others.

Product specifications are subject to change without notice and this document does not represent a commitment or guarantee on the part of Chyron and associated parties. This product is subject to the terms and conditions of Chyron's software license agreement. The product may only be used in accordance with the license agreement.

Any third party software mentioned, described or referenced in this guide is the property of its respective owner. Instructions and descriptions of third party software is for informational purposes only, as related to Chyron products and does not imply ownership, authority or guarantee of any kind by Chyron and associated parties.

This document is supplied as a guide for Chyron PRIME WebSocket Automation Interface. Reasonable care has been taken in preparing the information it contains. However, this document may contain omissions, technical inaccuracies, or typographical errors. Chyron and associated companies do not accept responsibility of any kind for customers' losses due to the use of this document. Product specifications are subject to change without notice.

Copyright © 2025 Chyron, ChyronHego Corp. and its licensors. All rights reserved.

Table of Contents

Interface Specification.....	4
API Overview.....	4
Assets/Projects API.....	4
Graphics/Clips API.....	5
Switcher API.....	7
Communication Protocol.....	10
Responses.....	12
Response Specification.....	12
Examples.....	12
Tools.....	12

Interface Specification

API Overview

interface Root

- Runtime Runtime { get; }
- ProjectManager Projects { get; }

interface Runtime

- Switcher Switcher { get; }
- IChannel[] Channels { get; }
- IClipPlayer[] ClipPlayers { get; }

Assets/Projects API

enum PathType

File,
Directory

interface IName

string Name { get; }

interface IPath : IName

PathType Type { get; }
string Path { get; }

interface IProject : IPath

interface ProjectManager

/// Returns the current project
IProject CurrentProject { get; }
/// Returns a list of all project names (same as available in combobox)
string[] AllProjects { get; }
/// Changes the current project for the application
void SetCurrentProject(string name)

Graphics/Clips API

```
enum PlayoutState
    Loading,
    Loaded,
    PlayPending
    Playing,
    Stopping,
    Stopped,
    Closing,
    Closed

interface ISize
    int Width, Height { get; }

interface IScene : IName
    InstanceId { get; }
    ISize Size { get; }
    float FrameRate { get; }
    IBitmap Thumbnail { get; }
    PlayoutState PlayoutState { get; }
    IReplaceable[] Replaceables { get; }
    IControlPanel ControlPanel { get; }
    bool Update(string name, object value);
    event PlayoutStateChanged(PlayoutState playoutState);
    event ReplaceableChanged(string id, string value);

    string[] Actions { get; } // Typically actions are only triggered through button control
                           // clicks
    void PlayAction(string action)

interface IReplaceable
    string Id { get; }
    string Type { get; } //String, Boolean, Int32, Double
    string Value { get; set; }

interface IPPoint
    int X, Y { get; }
```

```

interface IControl : IName
    string Type { get; } // Button, CheckBox, TextBox, ComboBox
    IPoint Location { get; }
    ISize Size { get; }
    object Value { get; }
    string ForeColor, BackColor { get; } // "#FF7F00" or "#7FFF7F00" with alpha
    string FontName
    float FontSize
    string FontStyle // "Bold", "Italic", or "Bold, Italic"
    IBitmap BackgroundImage // can be null

interface IControlPanel : IControl
    IControl[] Controls { get; }

interface IChannel
    string Name { get; }
    IScene[] OpenScenes { get; }
    IScene GetScene(int instanceId)
    void LoadScene(string path)
    void PlayScene(string path)
    void StopScene(string path)
    void CloseScene(string path)
    void CloseAllScenes()
    event PlayoutStateChanged(int instanceId, PlayoutState playoutState)
    event SceneAdded(IScene scene)
    event SceneRemoved(IScene scene)

enum ClipState
    None
    Cued
    Playing
    Paused

interface IClipScene : IScene
    ClipState ClipState { get; }
    float Rate { get; }
    int TotalFrames { get; }
    int CurrentFrame { get; }
    bool Loop { get; set; }
    event ClipStateChanged(ClipState clipState)

```

```
interface IClipPlayer : IChannel
    IClipScene CuedScene { get; }
    IClipScene PlayingScene { get; }
    void HomeCued()
    void PlayCued()
    void ClearCued()
    void HomePlaying()
    void PlayOrResumePlaying()
    void PausePlaying()
    void StopPlaying()
    void ClearPlaying()
    event ClipStateChanged(int instanceId, ClipState clipState)
```

Switcher API

enum SourceType

- Black
- VideoInput
- ClipPlayer
- Graphic
- Dve
- MixEffect

interface Source

- string Name { get; }
- int Index { get; }
- SourceType Type { get; }

interface Bus

- int Index { get; }
- int Layer { get; } // 0 for Preset, Program, 1-N for Key 1-N
- string Name { get; } // Preset, Program, Key1 - KeyN
- Source ActiveSource { get; }
- bool IsOnProgram { get; }
- event ActiveSourceChanged(Source source);
- event IsOnProgramChanged(bool onProgram);
- void SetActiveSource(string name);

interface AudioBus

- double Volume { get; set; }
- bool IsMuted { get; set; }
- /// Lowers volume by animating towards "scale * Volume"
 /// scale: applied to current volume to get new volume (0-1)
 /// frames: animation duration in frames. Optional: defaults to configured audio duck frame count
 void Duck(double scale, int? frames);
- /// Reverts volume to value before Duck
 /// frames: animation duration in frames. Optional: defaults to configured audio duck frame count
 void Unduck(int? frames);
- /// Fades volume to given level
- /// targetLevel: fade to this level (0-1)
 /// frames: duration in frames. Optional: defaults to configured audio duck frame count
 void Fade(double targetLevel, int? frames);

interface KeyBus : Bus

- void Cut()
- void AutoTrans()

interface Transfer

- int Index { get; }
- string Name { get; } // Background, Key1 - KeyN
- bool Enabled { get; set; }
- event EnabledChanged(Transfer transfer)

interface Bank

- string Name { get; }
- Bus[] Buses { get; } // all buses
- Transfer[] Transfers { get; }
- Bus Preset { get; }
- Bus Program { get; }
- Bus[] BackgroundBuses { get; } // Preset and Program
- KeyBus[] KeyBuses { get; }
- void Cut()
- string[] TransitionNames { get; }
- string ActiveTransition { get; }
- event ActiveTransitionChanged(string transitionName)
- void SetActiveTransition(string name)
- void AutoTrans()

- Transfer GetTransfer(string name)
- bool SetTransfer(string name, bool enabled)

interface Switcher

- Source[] Sources { get; }
- Bank[] Banks { get; } // all banks
- Bank Main { get; }
- Bank[] MixEffectBanks { get; }
- AudioBus[] AudioBuses { get; }
- AudioBus GetAudioBus(string name);
- Switcher GetState()

Communication Protocol

Each request is a JSON object containing the following fields:

Id: request identifier (positive integer), used to couple requests and responses within one connection. Always required.

Type: request type, one of following:

- `get`: retrieve value
- `set`: set value
- `call`: call method
- `attach`: add event handler, events are sent containing the id supplied as parameter
- `detach`: remove event handler

Can be omitted, in which case `call` is assumed.

Method: request path relative to connected endpoint. See API for available paths. Each part of the path is separated by a dot. Always required. Arrays can be indexed by placing the index inside parentheses at the end of the path. For function calls, the parentheses at the end must be omitted, they are implied by the `call` type.

Params: parameters for the request. Not allowed for `get` requests.

`set`: exactly one parameter must be supplied. This will be the new value.

`call`: number of parameters must match function parameters.

`attach`: exactly one parameter must be supplied. This can be any id which will be sent in event invocations.

`detach`: any number of parameters can be supplied. Without parameters all handlers will be removed for that path. Any parameter supplied must be an id that was previously attached, which will be detached.

Multiple requests can be sent at once by putting multiple request objects into a JSON array.

Examples

```
//send; connect to switcher: wss://1.2.3.4:5678/Runtime/Switcher
{ id: 1, type: "set", method: "Main.Transfers(0).Enabled", params: [ true ] } //
    Main.Transfers[0].Enabled = true;
{ id: 2, method: "Main.Cut" } // Cut();
{ id: 3, method: "Main.SetActiveTransition", params: [ "Dissolve" ] } //
    SetActiveTransition("Dissolve")
{ id: 9, method: "Main.Preset.SetActiveSource", "params": [ "GFX5" ] } //
    Main.Preset.SetActiveSource("GFX5");
{ id: 4, type: "get", method: "Main.Program.ActiveSource" } // return Program.ActiveSource;
{ id: 5, type: "attach", method: "Main.Preset.ActiveSourceChanged", params: [ 6 ] } //
    Program.ActiveSourceChanged += 6;
{ id: 7, type: "detach", method: "Main.Preset.ActiveSourceChanged", params: [ ] } //
    Program.ActiveSourceChanged -= 6;
{ id: 8, type: "get", method: "Sources(1)" } // return Sources[1];
{ id: 9, type: "call", method: "AudioBuses(0).Duck", params: [0.2] } // AudioBuses[0].Duck(0.2);

//send; connect to bus directly: wss://1.2.3.4:5678/Runtime/Switcher/Main
{ id: 1, type: "set", method: "Transfers(0).Enabled", params: [ true ] } // Transfers[0] = true;
{ id: 2, method: "Cut" } // Cut();
{ id: 3, type: "call", method: "SetActiveTransition", params: [ "Dissolve" ] } //
    SetActiveTransition("Dissolve")
{ id: 9, method: "Preset.SetActiveSource", "params": [ "GFX5" ] } //
    Main.Preset.SetActiveSource("GFX5");
{ id: 4, type: "get", method: "Program.ActiveSource" } // return Program.ActiveSource;
{ id: 5, type: "attach", method: "Preset.ActiveSourceChanged", params: [ 6 ] } //
    Program.ActiveSourceChanged += 6;
{ id: 7, type: "detach", method: "Preset.ActiveSourceChanged", params: [ 6 ] } //
    Program.ActiveSourceChanged -= 6;

// allow array of commands to be sent
[
{ id: 1, type: "get", method: "Preset.Source", params: [ "CAM1" ] },
{ id: 2, method: "Cut" }
]
```

Responses

Each request sent triggers a response. Attached event handlers also send these response objects.

Response Specification

This response is a JSON object containing the following fields:

Id: the request id used to trigger the request. If no id was supplied (invalid request) this will be -1. For event handlers this will be the supplied parameter.

Error: an object containing two fields: `Code` (integer) and `Message` (string). Only present if the request fails.

Result: the value returned by a `get` request, omitted for other request types

Params: the event parameters. Only present for event callbacks.

Examples

```
//receive
{ Id: 3 }
{ Id: 4, Result: { Index: 0, Type: "Input", Name: "CAM1" } }
{ Id: 5 }
{ Id: 6, Params: [ { Name: "Program", Source: "CAM2" } ] }
{ Id: 7 }
{ Id: 9, Error: { Code: 123, Message: "Invalid command" } }
```

Tools

The API can easily be tested from the browser using this page:

[websocketclient.html](#)

ABOUT US

Chyron is ushering in the next generation of storytelling in the digital age. Founded in 1966, the company pioneered broadcast titling and graphics systems. With a strong foundation built on over 50 years of innovation and efficiency, the name Chyron is synonymous with broadcast graphics. Chyron continues that legacy as a global leader focused on customer-centric broadcast solutions. Today, the company offers production professionals the industry's most comprehensive software portfolio for designing, sharing, and playing live graphics to air with ease. Chyron products are increasingly deployed to empower OTA & OTT workflows and deliver richer, more immersive experiences for audiences and sports fans in the arena, at home, or on the go.

CONTACT SALES

EMEA • North America • Latin America • Asia/Pacific
+1.631.845.2000 • sales@chyron.com

