

Prime Plugin User Guide

Version 4.10.10

September 2025



Chyron Prime Plugin User Guide • 4.10.10 • September 2025 • This document is distributed by Chyron in online (electronic) form only, and is not available for purchase in printed form.

This document is protected under copyright law. An authorized licensee of Chyron Prime Plugin may reproduce this publication for the licensee's own use in learning how to use the software. This document may not be reproduced or distributed, in whole or in part, for commercial purposes, such as selling copies of this document or providing support or educational services to others.

Product specifications are subject to change without notice and this document does not represent a commitment or guarantee on the part of Chyron and associated parties. This product is subject to the terms and conditions of Chyron's software license agreement. The product may only be used in accordance with the license agreement.

Any third party software mentioned, described or referenced in this guide is the property of its respective owner. Instructions and descriptions of third party software is for informational purposes only, as related to Chyron products and does not imply ownership, authority or guarantee of any kind by Chyron and associated parties.

This document is supplied as a guide for Chyron Prime Plugin. Reasonable care has been taken in preparing the information it contains. However, this document may contain omissions, technical inaccuracies, or typographical errors. Chyron and associated companies do not accept responsibility of any kind for customers' losses due to the use of this document. Product specifications are subject to change without notice.

Copyright © 2025 Chyron, ChyronHego Corp. and its licensors. All rights reserved.

Table of Contents

IPlugin Interface..... 5

 PluginObjectDefinition Struct..... 5

 ObjectType Definition..... 5

 PluginEffectBase Abstract Class..... 6

 PluginObjectBase Abstract Class..... 6

 EditorType Definition..... 6

 RuntimeType Definition..... 7

 IPluginSettings Interface..... 7

Introduction to Prime Plugin

The Prime Graphics Platform defines a plugin architecture that allows for custom behavior to extend the usability of the software using .NET classes created in Visual Studio. This includes the ability to define: custom objects and effects that can be added to scenes, editors to adjust values for these objects and effects, runtime logic for the objects and effects, custom application-wide settings for the plugin, and editors to adjust values for the application wide settings.

To begin, create a new Class Library project in Visual Studio targeting the 4.10.5 version of the .NET Framework. In the References section, add references to the following libraries from the C:\Program Files\ChyronHego\Prime x.x.x\ folder:

ChyronHego.Prime.Plugin
ChyronHego.Prime.Scene
ChyronHego.Prime.Syntax
ChyronHego.Framework.Application
ChyronHego.Enterprise.Infrastructure

The Prime software will attempt to load all libraries located in the C:\Chyron\Prime\Plugins folder if it exists. For each library that is successfully loaded, a plugin will be instantiated for each class that implements the IPlugin interface in the ChyronHego.Prime.Plugin namespace.

IPlugin Interface

Add a new class to the project and have it implement the IPlugin interface. See the SamplePlugin.cs class in the SamplePlugin project for an example of this. The IPlugin interface defines 3 members that must be implemented:

```
string Name { get; }  
IEnumerable<PluginObjectDefinition> ObjectDefinitions { get; }  
IPluginSettings Settings { get; }
```

Name defines the name of the plugin. ObjectDefinitions defines a list of objects that can be placed within Prime scenes. Settings defines an object that can be used to edit and save application-wide settings for the plugin. Name must return a valid string. ObjectDefinitions can return an empty list, and Settings can return null if not needed.

PluginObjectDefinition Struct

The PluginObjectDefinition struct defines the name, object type, editor type and runtime type to be used with a plugin object:

```
public string Name { get; set; }  
public Type ObjectType { get; set; }  
public Type EditorType { get; set; }  
public Type RuntimeType { get; set; }
```

Name must return a valid string and ObjectType must return the type of a valid plugin object. EditorType and RuntimeType can both return null if not needed.

ObjectType Definition

Prime supports two types of objects that can be saved within scenes: Effects and Resources. Effects can be added as children of Graphic objects, allowing for behavior that can alter the parent graphic in some way, while Resource objects can be added to the Resources section of the scene to perform changes on the scene as a whole. The main purpose of this object type definition is to define the various properties that should be saved with this object.

PluginEffectBase Abstract Class

To create a type that represents an Effect, add a class to the project that inherits from `PluginEffectBase` in the `ChyronHego.Prime.Plugin.Objects` namespace. For example, the `SamplePlugin` project defines a `TimeZonePluginEffect` class that inherits from `PluginEffectBase`, while also defining a custom `TimeZoneld` string property. This effect was designed to update a parent `Text` object to display the time of the time zone specified in the effect.

PluginObjectBase Abstract Class

To create a type that represents a Resource, add a class to the project that inherits from `PluginObjectBase` in the `ChyronHego.Prime.Plugin.Objects` namespace. For example, the `SamplePlugin` project defines an `OffsetPluginObject` class that inherits from `PluginObjectBase`, while also defining a custom `MinutesOffset` integer property. This object was designed to store a minutes offset value that all `TimeZonePluginEffect` objects can look for, and if found, offset the time zone by the specified number of minutes.

For each defined `PluginObjectDefinition`, set the `ObjectType` property to the type of the created effect or resource class.

EditorType Definition

Each plugin object can define an optional editor type that will be displayed in the Properties section of the Prime Designer when the object is selected, and allows editing the values of the properties defined with the object. To create a plugin object editor, add a new User Control (Windows Forms) to the project. After the user control has been added, change the base type of the class file from `UserControl` to `PluginEditorBase` defined in the `ChyronHego.Prime.Plugin.Editor` namespace. Note: this base class already inherits from `UserControl`. Before this editor is shown for the defined plugin object, the `PluginObject` property will be set with the instance of the selected plugin object. This property can be overridden to set up any necessary data binding for the designed property editors.

For example, the `SamplePlugin` project contains a `TimeZonePluginEditor` user control that inherits from `PluginEditorBase`, and displays a combo box that is populated with all known system time zones, and contains code to bind the `TimeZoneld` property of the `TimeZonePluginEffect` class to this combo box.

For each defined `PluginObjectDefinition`, set the `EditorType` property to the type of the created user control that corresponds with the object type.

RuntimeType Definition

Each plugin object can define an optional runtime class that will be instantiated when a scene is loaded on a playout channel. To create a runtime class, add a new Class to the project, and set the class to inherit from `PluginRuntimeBase` defined in the `ChyronHego.Prime.Plugin.Runtime`. This class provides a `PluginObject` property that can be overridden to access the plugin object that should be operated on. It also defines `Load`, `Play`, `Stop` and `Clear` methods that can be overridden to provide custom runtime behavior for the plugin object.

For example, the `SamplePlugin` project contains a `TimeZonePluginRuntime` class that provides behavior to update the parent text object of the associated `TimeZonePluginEffect` with the current time for the time zone of the effect's property.

IPluginSettings Interface

To define application-wide settings for the plugin, a class type can be specified for the `Settings` property of the main plugin class. This class must implement the `IPluginSettings` interface in the `ChyronHego.Prime.Plugin.Settings` namespace with the following properties:

```
string Name { get; }  
Image Image { get; }  
Type EditorType { get; }
```

`Name` and `Image` defines the name and image to be displayed in the application settings item list on the left hand side. `EditorType` defines the type of user control to be created to edit the settings.

ABOUT US

Chyron is ushering in the next generation of storytelling in the digital age. Founded in 1966, the company pioneered broadcast titling and graphics systems. With a strong foundation built on over 50 years of innovation and efficiency, the name Chyron is synonymous with broadcast graphics. Chyron continues that legacy as a global leader focused on customer-centric broadcast solutions. Today, the company offers production professionals the industry's most comprehensive software portfolio for designing, sharing, and playing live graphics to air with ease. Chyron products are increasingly deployed to empower OTA & OTT workflows and deliver richer, more immersive experiences for audiences and sports fans in the arena, at home, or on the go.

CONTACT SALES

EMEA • North America • Latin America • Asia/Pacific
+1.631.845.2000 • sales@chyron.com

